

Multiple Effect Rocket System (MERS) Illumination Rocket, 600m



Application

- Illumination of the fore field
- Illumination during search and rescue operations
- Signalling purpose

Description:

Smokeless burning of the rocket propellant results in minimal signature at initiation combined with no visible signature throughout flight providing concealment from detection of launch. Flight tube design and induced tail spin provide high level of accuracy. The store architecture requires no stored energy in the initiator. Twist initiation provides for both left & right hand operation.

Operation:

MERS incorporates a 3 stage safety system comprising of:

1. Turn twist initiator clockwise from Safe Position "S" into Armed-Position "A". This action unlocks the twist initiator allowing it to be pulled in axial direction.
2. Pull twist initiator from Armed-Position into Firing-Position "F". This action unlocks the twist initiator allowing it to be rotated clockwise or counter-clockwise.
3. Twist initiation clockwise or counter-clockwise to fire the rocket.

Provided the twist initiator has not been rotated, MERS can be returned to the safe condition.

Specifications:

Length:	260mm
Diameter:	51mm
Weight:	Approx. 530g
Recoil:	<500 N
Flare altitude at firing angle 45°:	200m
Range:	600m
Burning time:	30 Sec
Light intensity:	≥ 200.000 cd
Wavelength:	589±3 nm

References:

N/A

Product Codes:

9166200

NATO Stock Numbers:

TBA

UN Number:

UN 0254

Proper shipping name:

Ammunition, Illuminating

Packing:

10 rockets packed in a steel box (4A), type PA19

Qty. per box	Hazard Class	NEQ (kg)	GR Wgt (kg) approx.	Vol m ³ approx.
10	1.3 G	1.5kg	8.6kg	0.012m ³

This is the standard method of pack. Other packs may be available subject to specification. Please contact our sales team to discuss your requirements